

# ADVANCED MANUAL CRITICAL POINT DRYER

## **SAMDRI<sup>®</sup>-PVT-3D**



**tousimis**

The Advanced Manual **SAMDRI<sup>®</sup>-PVT-3D** delivers highly reproducible results via manual controls. The Micro-Metering Valves and control panel are conveniently located for ease of operator control. Automatic critical point temperature and pressure regulation are standard features with the Advanced Manual **SAMDRI<sup>®</sup>-PVT-3D**.

# Samdri®-PVT-3D

(ADVANCED MANUAL CRITICAL POINT DRYER)

Catalog # 8755B



## FEATURES

- Compact tabletop size with small footprint.
- Precise flow control via Micro Metering valves.
- Vernier handles on metering valves enable reproducible flow settings.
- EZ top loading process chamber.
- Under-lit chamber with view port enables visualization of chamber status.
- Internal 0.5µm particulate filtration\* protect samples and valves.
- Internal surfaces inert to LCO<sub>2</sub> and ultra-pure alcohols.
- Tough, solvent resistant cabinet.
- Automatic critical point temperature - pressure regulation for system safety.
- Fast adiabatic chamber cooling\* with CO<sub>2</sub> (<1 minute @ room temperature).
- All electronic and other components meet UL, CE and/or U.S. Military Specifications.
- Optional SOTER™ Condenser\* may be attached to capture waste alcohol and



SEM of the internal surface of the carotid (human) artery. This samdried (critical point dried) sample shows not only surface membrane details but also endothelial cell boundaries and their nuclei.

## SPECIFICATIONS

- Cabinet Size: 12.75"(W) x 9.75"(H) x 18.50"(L)  
32.4cm(W) x 24.8cm(H) x 47.0cm(L)
- System Set-Up Area Requirement: 20"(W) x 30"(D)  
51cm(W) x 76cm(D)
- Process Chamber size: 1.25" I.D. x 1.25" Depth
- Temperature gauge range: -30°C to 60°C
- Pressure gauge range: 0 to 2,000 psi.
- 120V / 50-60Hz (Other voltage units also available - Please inquire).



Optional SOTER™ Condenser\* (Cat# 8777)  
Quietly captures waste alcohol.

## STANDARD ACCESSORIES

- Flexible High-Pressure braided stainless steel inert Teflon® lined LCO<sub>2</sub> Supply Hose, 5ft (approximate 1.5m) long.
- External LCO<sub>2</sub> filtration system (#8784) removes water/oil and particulates down to 0.5µm. Filter Housing (#8784) is conveniently pre-installed onto your LCO<sub>2</sub> High Pressure Hose.
- Static free exhaust tubing for the PURGE/VENT/BLEED and COOL exhaust outlets.
- Flow Meter supplied allows precise periodic BLEED exhaust rate flow control.
- Spare chamber O-ring (2), chamber lamps (2), and 5A slo-blow fuses (2).
- User Manual and Check-Out Data Sheet.
- 2 year warranty on all parts and labor.
- Free lifetime technical support.



LCO<sub>2</sub> Filter Housing (#8784)  
installed onto High Pressure Hose

Visit our web site at [tousimis.com](http://tousimis.com) or contact us about the various sample holders.

\* U.S. patented (# 6,493,964) or patent pending.

Note: Actual delivered model or accessories may vary slightly, as advancements are constantly being applied.